

MicroJet Pump & Accessories

MicroJet Pump for Freshwater Applications

P/N 87013



- Centrifugal pump & stainless steel pump shaft & casing
- Built in .7 gallon pressure tank
- Motor is TEFC, 115VAC, 1 Phase, 0.2 Amps, 1000 Watts
- Maximum pressure: 65 PSI flowing
- Maximum system pressure: 109 PSI
- Run dry protection
- Extremely quiet
- Capacity: 19 GPM
- Suction lift: 25 feet
- Water inlet 1.0" & water outlet 1.0"
- Weight 34 pounds

Inlet Water Strainer

P/N 87015



- Corrosion-resistant nylon strainers
- Type 304 stainless steel screen
- White nylon head
- Buna-N O-rings
- Clear nylon bowl for see-through visibility
- Maximum Pressure: 150 PSI @ 70° F
- Maximum Temperature: 125° F
- 1" NPT Female
- Dimensions: End to End 4 61/64" & Overall Height 6 13/32"

Water Pressure Gauge

P/N 37029



- 0-100 PSI pressure range
- 1 1/2" polycarbonate dial
- Temperature Range: -4° F to +140° F Ambient
- Refillable glycerin-filled gauges dampens needle vibration
- Gauges have a dual scale that reads in PSI and kPa

Water Check Valve

P/N 40057



- Inlet/out pipe size: 1" NPT Female
- Maximum pressure: 150 PSI
- Maximum temperature: 140° F
- Valve body PVC
- Stem and spring are 18-8 stainless steel
- EPDM Seal

 **Microphor**
A Wabtec company
452 East Hill Road
Willits, CA 95490 USA
Tel: 707.459.5563
Tel: 800.358.8280
Fax: 707.459.6617
www.microphor.com
www.wabtec.com

CHANGES IN DESIGN - Continuing a policy of research and development, Microphor reserves the right of price, product, or design change without notice of obligation.

Form: 641
Rev: 10/04