

MicroJet Accessories

Water Pressure Accumulator Tanks

All covered by 5 year product warranty

Pre-Charged Bladder Tanks



- NSF approved
- FDA approved butyl rubber double inner diaphragm
- External shell is welded cold steel
- System connects are corrosion resistant stainless steel
- Maximum working pressure: 125 PSI
- Maximum liquid temperature: 160°F

Part No	Gallon Capacity	Drawdown in gallons		Dimensions		
		@30-50psi	@ 40-60psi	Diameter	Height	Length
72036	2.1	0.7	0.6	9"	11.25"	-
72037	8.5	2.6	2.3	12.625"	14"	19.25"

Pre-Charged Fiberwound Tanks



- UL classified to ANSI/NSF Standard 61 Drinking Water Components
- Use with fresh or salt water
- Extremely durable, rust, dent and scratch resistant
- Composite material is tougher than steel at half the weight
- Overlapping, continuous fiberglass strands sealed with epoxy resin
- One piece polyethylene base rotates 360°
- Inner line is one piece high density polyethylene
- Maximum working pressure: 100 PSI
- Maximum liquid temperature: 120°F

Part No.	Gallon Capacity	Drawdown in gallons		Dimensions		Weight
		@30-50psi	@ 40-60psi	Diameter	Height	
72040	20	5.9	5.2	16"	36"	28#
72041	35	10.3	9	20"	39.5"	38#
72042	60	17.7	15.5	24"	45.75"	70#



452 East Hill Road
Willits, CA 95490 USA
Tel: 707.459.5563
Tel: 800.358.8280
Fax: 707.459.6617
www.microphor.com
www.wabtec.com

CHANGES IN DESIGN - Continuing a policy of research and development, Microphor reserves the right of price, product, or design change without notice of obligation.

Form: 642
Rev: 10/04